

# Contents

I

## Challenges of a Precision Engineer

<b>1</b>	<b>Speak the right language</b> .....	<b>3</b>
1.1	Translate requirements to specifications	3
1.2	<b>Definitions</b>	<b>4</b>
1.2.1	Degrees of freedom .....	4
1.2.2	Target, true and observed value .....	5
1.2.3	Resolution .....	6
1.2.4	Tolerance and allowance .....	6
1.2.5	Precision, repeatability, reproducibility, trueness and accuracy .....	7
1.3	<b>Schematic representation</b>	<b>8</b>
1.3.1	Schematic representation of basic elements .....	9
1.3.2	The use of schematic representations throughout this book .....	10
<b>2</b>	<b>Comprehend physical effects</b> .....	<b>13</b>
2.1	Compliance or lack of stiffness	13
2.2	Inertia	14
2.3	Thermal effect	15
2.4	Shortening effect	16
2.5	Play	17
2.6	Friction, stick, spin, slip and sliding	18
2.7	Vibrations	23

<b>2.8</b>	<b>Hysteresis, virtual play and micro-slip</b>	<b>25</b>
2.8.1	Hysteresis . . . . .	25
2.8.2	Virtual play . . . . .	26
2.8.3	Micro-slip . . . . .	28
<b>2.9</b>	<b>Other physical effects</b>	<b>31</b>
<b>3</b>	<b>Select optimal strategies . . . . .</b>	<b>33</b>
<b>4</b>	<b>Predict system behaviour . . . . .</b>	<b>39</b>

## II **Toolbox of a Mechanical Engineer**

<b>5</b>	<b>System stiffness . . . . .</b>	<b>43</b>
<b>5.1</b>	<b>Parallel and series</b>	<b>43</b>
<b>5.2</b>	<b>Effect of a spring at another location</b>	<b>45</b>
5.2.1	Effect of a translational spring at the point of interest . . . . .	45
5.2.2	Effect of a rotational spring at the axis of interest . . . . .	46
5.2.3	Effect of a translational spring at the axis of interest . . . . .	47
5.2.4	Effect of a rotational spring at the point of interest . . . . .	49
<b>5.3</b>	<b>Energy method</b>	<b>49</b>
5.3.1	How to use the energy method . . . . .	49
5.3.2	Example: stiffness of a truss . . . . .	51
5.3.3	Example: stiffness of a shaft . . . . .	52
5.3.4	Example: stiffness of multiple springs in a circular layout . . . . .	54
<b>5.4</b>	<b>Systems with a preload</b>	<b>55</b>
<b>5.5</b>	<b>Centre of stiffness</b>	<b>56</b>
<b>6</b>	<b>Element stiffness and loadability . . . . .</b>	<b>57</b>
<b>6.1</b>	<b>Rotational stiffness for torsion</b>	<b>58</b>
6.1.1	Twisting, warping and stiffening effect . . . . .	58
6.1.2	Torsional and warping stiffness . . . . .	60
<b>6.2</b>	<b>Rotational stiffness for bending</b>	<b>66</b>
6.2.1	Cantilever beam subjected to a bending moment . . . . .	66
6.2.2	Simply supported beam subjected to a moment . . . . .	66
6.2.3	Composed beam subjected to a moment . . . . .	67
<b>6.3</b>	<b>Translational stiffness for lateral deformation</b>	<b>71</b>
6.3.1	Cantilever beam subjected to a transverse force . . . . .	71
6.3.2	Simply supported beam subjected to a transverse force . . . . .	73
6.3.3	Cantilever beam forced into a straight lateral displacement . . . . .	74

<b>6.4</b>	<b>Translational stiffness for longitudinal deformation</b>	<b>77</b>
6.4.1	Beam subjected to a longitudinal force . . . . .	77
6.4.2	Composed beam subjected to a longitudinal force . . . . .	77
6.4.3	Cantilever beam subjected to eccentric longitudinal force . . . . .	77
6.4.4	Deformed composed beam subjected to longitudinal force . . . . .	79
6.4.5	Loadability for compression . . . . .	81
<b>7</b>	<b>Contact stiffness and loadability . . . . .</b>	<b>87</b>
<b>7.1</b>	<b>Models for point and line contacts</b>	<b>88</b>
<b>7.2</b>	<b>Approximating stiffness and loadability</b>	<b>89</b>
7.2.1	Transferring variables to a set of parameters . . . . .	89
7.2.2	Stresses, deformation and stiffness for point contacts . . . . .	91
7.2.3	Stresses, deformation and stiffness for line contacts . . . . .	93
<b>8</b>	<b>Parasitic displacement . . . . .</b>	<b>95</b>
<b>8.1</b>	<b>Parasitic displacement due to shortening</b>	<b>95</b>
<b>9</b>	<b>Static behaviour . . . . .</b>	<b>97</b>
<b>9.1</b>	<b>Static characteristics</b>	<b>97</b>
9.1.1	Static characteristics of basic elements . . . . .	97
9.1.2	Static characteristics of some basic systems . . . . .	98
9.1.3	Total play in systems with multiple springs . . . . .	106
9.1.4	Example of static characteristic . . . . .	106
<b>9.2</b>	<b>Systems with micro-slip</b>	<b>111</b>
9.2.1	Micro-slip in a clamp . . . . .	111
9.2.2	Micro-slip in a bolted joint . . . . .	115
9.2.3	Micro-slip in a belt drive . . . . .	115
<b>10</b>	<b>Dynamic behaviour . . . . .</b>	<b>119</b>
<b>10.1</b>	<b>Free vibration in the time domain</b>	<b>119</b>
10.1.1	Free vibration without damping . . . . .	119
10.1.2	Free vibration with viscous damping . . . . .	120
<b>10.2</b>	<b>Forced vibration in the time domain</b>	<b>122</b>
10.2.1	Forced vibration without damping . . . . .	123
10.2.2	Forced vibration with viscous damping . . . . .	125
<b>10.3</b>	<b>Forced vibration in the frequency domain</b>	<b>127</b>
<b>10.4</b>	<b>Analysis of damping</b>	<b>128</b>
10.4.1	Relation between damping ratio and specific damping capacity .	129
10.4.2	Relation between damping ratio and decrement for free vibration	130
10.4.3	Relation between damping ratio and 3dB-bandwidth . . . . .	130

10.4.4	Graphical representation of $\zeta$ in a root locus plot . . . . .	131
--------	--	-----

## **11 Thermal behaviour . . . . . 133**

### **11.1 Temperature change 133**

11.1.1	Effect of change in temperature on homogeneous object . . . . .	133
--------	---	-----

11.1.2	Effect of change in temperature on bimaterial object . . . . .	135
--------	--	-----

11.1.3	Effect of change in energy on temperature . . . . .	136
--------	---	-----

### **11.2 Energy transfer by heat 137**

11.2.1	Thermal radiation . . . . .	137
--------	-----------------------------	-----

11.2.2	Conduction . . . . .	137
--------	----------------------	-----

11.2.3	Radiation versus conduction . . . . .	138
--------	---------------------------------------	-----

## **III Design strategies for precision engineering**

## **12 Low stress relationships . . . . . 141**

### **12.1 Introduction to degrees of freedom 141**

### **12.2 Design exact-constraint 145**

12.2.1	Why design exact-constraint . . . . .	145
--------	---------------------------------------	-----

12.2.2	Basic elements for constraining . . . . .	148
--------	---	-----

12.2.3	Elements in parallel . . . . .	151
--------	--------------------------------	-----

12.2.4	Elements in series . . . . .	153
--------	------------------------------	-----

12.2.5	Analysing degrees of freedom . . . . .	156
--------	--	-----

12.2.6	Designing degrees of freedom . . . . .	157
--------	--	-----

12.2.7	Degrees of freedom exercises . . . . .	157
--------	--	-----

12.2.8	Adding redundant constraints . . . . .	158
--------	--	-----

12.2.9	Methods for analysing degrees of freedom . . . . .	159
--------	--	-----

### **12.3 Use elastic averaging 159**

### **12.4 Avoid a step in the stiffness 161**

## **13 Minimise deviation . . . . . 163**

### **13.1 Minimise load on the system 163**

13.1.1	Use a force-frame . . . . .	164
--------	-----------------------------	-----

13.1.2	Strive for a constant temperature . . . . .	164
--------	---	-----

13.1.3	Neutralise acceleration forces . . . . .	165
--------	--	-----

13.1.4	Reduce impact forces . . . . .	166
--------	--------------------------------	-----

13.1.5	Isolate vibrations . . . . .	166
--------	------------------------------	-----

13.1.6	Minimise friction . . . . .	167
--------	-----------------------------	-----

<b>13.2</b>	<b>Strive for a high stiffness</b>	<b>167</b>
13.2.1	Aim for a favourable transmission ratio . . . . .	167
13.2.2	Design in parallel . . . . .	168
13.2.3	Optimise stiffnesses of compliant elements in series . . . . .	169
13.2.4	Choose a short force path . . . . .	169
13.2.5	Apply loads in stiff directions . . . . .	170
13.2.6	Strive for a high torsional stiffness . . . . .	172
13.2.7	Strive for a high element stiffness . . . . .	174
13.2.8	Strive for a high contact stiffness . . . . .	175
<b>13.3</b>	<b>Strive for a low mass</b>	<b>178</b>
13.3.1	Aim for lightweigt and stiff . . . . .	179
13.3.2	Use two-stage systems . . . . .	187
<b>13.4</b>	<b>Strive for a high damping</b>	<b>188</b>
13.4.1	Viscous damping . . . . .	189
13.4.2	Coulomb damping . . . . .	191
13.4.3	Hysteretic damping . . . . .	191
13.4.4	Eddy current damping . . . . .	194
13.4.5	Tuned mass damping . . . . .	194
<b>13.5</b>	<b>Strive for thermal stability</b>	<b>198</b>
13.5.1	Aim for zero or equal deformation . . . . .	198
13.5.2	Choose the optimal location for the centre of thermal expansion . . . . .	199
<b>13.6</b>	<b>Eliminate or minimise position errors</b>	<b>200</b>
13.6.1	Use symmetric designs . . . . .	200
13.6.2	Average errors . . . . .	202
13.6.3	Compensate for undesirable displacement . . . . .	203
<b>13.7</b>	<b>Optimise measurement and control</b>	<b>204</b>
13.7.1	Use a metro-frame . . . . .	204
13.7.2	Aim for an optimal measurement . . . . .	205
13.7.3	Choose optimal position for actuator and sensor . . . . .	206
13.7.4	Correct the control value . . . . .	208
<b>14</b>	<b>Prevent relative movement . . . . .</b>	<b>209</b>
<b>14.1</b>	<b>Avoid (micro-)slip</b>	<b>209</b>
14.1.1	Design monolithic systems . . . . .	209
14.1.2	Use screwing . . . . .	210
14.1.3	Use adhesives or welding . . . . .	210
14.1.4	Avoid difference in strain . . . . .	211
<b>14.2</b>	<b>Minimise difference in strain</b>	<b>212</b>
14.2.1	Align neutral lines for bending . . . . .	212
14.2.2	Optimise clamping . . . . .	212

<b>14.3</b>	<b>Add preload</b>	<b>214</b>
14.3.1	Avoid play . . . . .	214
14.3.2	Provide preload force . . . . .	215
<b>14.4</b>	<b>Prevent movement in one direction</b>	<b>216</b>
<b>15</b>	<b>Facilitate relative movement . . . . .</b>	<b>217</b>
<b>15.1</b>	<b>Avoid all mechanical contact</b>	<b>217</b>
15.1.1	Avoid physical contact using ferrofluid bearings . . . . .	218
15.1.2	Avoid physical contact using hydrostatic bearings . . . . .	219
15.1.3	Avoid physical contact using aerostatic bearings . . . . .	219
15.1.4	Avoid physical contact using magnetic bearings . . . . .	219
<b>15.2</b>	<b>Use flexure mechanisms</b>	<b>220</b>
15.2.1	Use sheet flexure as hinge . . . . .	221
15.2.2	Use cross flexures as hinge . . . . .	222
15.2.3	Use parallel flexures as linear guide . . . . .	224
15.2.4	Reinforced flexures with mid-section . . . . .	226
15.2.5	Use notch hinges . . . . .	226
15.2.6	Aim for low or zero stiffness . . . . .	229
<b>15.3</b>	<b>Optimise sliding</b>	<b>231</b>
15.3.1	Minimise friction force . . . . .	231
15.3.2	Minimise the effects of wear . . . . .	232
<b>15.4</b>	<b>Optimise rolling</b>	<b>234</b>
15.4.1	Rolling bearings . . . . .	234
15.4.2	Strive for pure rolling . . . . .	235
15.4.3	Rolling in a hinge . . . . .	236
<b>16</b>	<b>Manage energy . . . . .</b>	<b>239</b>
<b>16.1</b>	<b>Store energy</b>	<b>239</b>
16.1.1	Store kinetic energy by using a balance mass . . . . .	239
16.1.2	Store elastic potential energy by using springs . . . . .	240
16.1.3	Store potential energy by using a mass and a spring . . . . .	241
<b>16.2</b>	<b>Dissipate energy</b>	<b>243</b>
16.2.1	Use friction for braking . . . . .	243
16.2.2	Use eddy current braking . . . . .	243
16.2.3	Use plastic deformation . . . . .	243

## IV Design concepts for precision designs

<b>17</b>	<b>Linear guiding</b> .....	<b>247</b>
17.1	Parallel sheet flexures as linear guide	247
17.2	Carriage with V-groove on rail with spindel drive	249
17.3	Carriage with V-groove with magnetic drive, AAE	251
17.4	Slide with ball screw, University of Twente	253
17.5	Conveyor belt for linear motion	253
17.6	Conveyor belt for positioning, Sioux-CCM	257
<b>18</b>	<b>Manipulating and adjusting</b> .....	<b>261</b>
18.1	Manipulators with a high transmission ratio	261
18.2	Mechanisms with notch hinges	262
18.3	Manipulator for six degrees of freedom	263
18.4	Adjustment in two DOF in a printhead, NTS	264
<b>19</b>	<b>High dynamic positioning</b> .....	<b>267</b>
19.1	Positioning of crystals, MI Partners	267
19.2	High dynamic manipulating of optical stage, JPE	272
<b>20</b>	<b>Torque transmission</b> .....	<b>275</b>
20.1	Coupling of suspended shafts with one rod	275
20.2	Coupling of suspended shafts using four flexures	276
20.3	Coupling of suspended shafts with a hollow tie rod	277
20.4	Helical coupling in a printer, Canon	277
20.5	Self centring couplings	278

## V Appendices

<b>A</b>	<b>Efficiency of beams</b> .....	<b>283</b>
<b>B</b>	<b>Answers to exercises</b> .....	<b>289</b>
<b>C</b>	<b>Tables</b> .....	<b>291</b>
	<b>Bibliography</b> .....	<b>297</b>

<b>Index</b> .....	<b>303</b>
--------------------	------------